Garment Processing & Laundry Equipments



Pioneer Side Load Washing Machine

Side load washing machine is suitable for washing of garments, denim/enzyme wash, garment dyeing, dyeing of knitted garments, washing of cotton fabrics.

Salient Features -

- -Machine has automatic panel with features like auto reverse, auto forward, automatic digital temp. indicator, auto timed.
- -Auto digital temperature control and auto stop features with gear box drive.
- -The body of machine is fabricated out of stainless steel grade 304/316.
- -The inner drum basket is made of perforated stainless steel of 304 grade , having a single smooth joint.

Pioneer's side load washing machine is designed for minimum liquor

ratio ,hence saving water and chemical usage , and provides with better quality fabric.



Pioneer Side Load Washing Machine

| - U | | | | | | | | |
|-------------------------------|----------|----------|-----------|-----------|-----------|-----------|-----------|-----------|
| Model | SL-15 | SL-30 | SL-100 | SL-150 | SL-175 | SL-200 | SL-300 | SL-400 |
| Capacity (kg) | 15 | 30 | 100 | 150 | 175 | 200 | 300 | 400 |
| Basket Size (dia x depth)(mm) | 610x710 | 750x950 | 1150x1380 | 1060x2440 | 1372x1524 | 1220x2490 | 1220x3660 | 1500x3660 |
| Basket Vol. (ltrs.) | 200 | 420 | 1435 | 2150 | 2625 | 2850 | 4275 | 6465 |
| Loading Doors Opening | 520X 300 | 520X 400 | 665X 470 |
| No of Doors | 1 | 1 | 1 | 1 | 1 | 2 | 3 | 3 |
| Drive Motors (kw) | 0.37 | 0.75 | 5.60 | 7.50 | 7.5 | 15 | 15 | 18.75 |
| Water Connection | 1" BSP | 1.5" BSP | 2" BSP | 2" BSP | 2" BSP | 2" BSP x2 | 2" BSP x3 | 2" BSP x3 |
| Water Consumption/dip (ltrs) | 85 | 210 | 700 | 1060 | 1349 | 1499 | 2200 | 3250 |
| Drain (inch) | 3" | 3" | 4" | 4" | 6" | 6" | 8.5" | 8.8" |
| Steam Connection | 15mm | 15mm | 15mm | 20mm | 20mm | 25mm | 25mm x2 | 25mm x2 |
| Diesel Fired (Ltrs.) | 1-1.5 | 1.5-2 | 5 -6.2 | 6.5-7.25 | 7.5-8.75 | 7-9 | N.A. | N.A. |
| Width (mm) | 1790 | 2050 | 2770 | 3425 | 3600 | 3950 | 5400 | 5600 |
| Depth (mm) | 760 | 965 | 1400 | 1350 | 1400 | 1470 | 1730 | 2040 |
| Height (mm) | 1100 | 1310 | 1550 | 1400 | 1550 | 1600 | 1700 | 2000 |
| Weight (kg) | 520 | 800 | 1325 | 1950 | 2250 | 2675 | 4135 | 5250 |
| | | | | | | | | |